

**TurboWedge Genealogy**

<b>Terminal Manufacturer</b>	<b>Terminal Type</b>	<b>Model</b>	<b>Cable Number</b>	<b>ID</b>	<b>Keyboard Primary - Secondary Comments</b>
APPLE	Macintosh	1 / 2	02TC005	29	/CAPLK CAPLK
CLI	5476/5488v	1 / 2	02TC001	64	CLI 122 Cherry /CAPLK CAPLK PWR with TW2
CLI	ET 2000, 5476/5488v	1 / 2	02TC002	01 01 08	CLI 122 soft touch 101 102 122Key-IBM style PWR with TW2
CLI	ET 3000w	1 / 2	02TC002	01	CLI 122 or 101/104 Kbd PWR with TW2
DEC	2XX,3XX,4XX	1 / 2	02TC011	15	T/W
DECISION DATA	386	1 / 2	02TC001	08	/CAPLK CAPLK
	387C	1 / 2	02TC001	08	/CAPLK CAPLK
	3496	2	02TC002	39	T/W
	3497	2	02TC002	09	T/W
	3596/97 - 83K	2	02TC006	62	/SHLK SHLK PWR with Laser
	3596/97 - 102K	2	02TC006	63	/CAPLK CAPLK PWR with Laser
	3596/97 - 122K	2	02TC006	60	/CAPLK CAPLK PWR with Laser
	3596 with 3776 Keyboard	2	02TC006	64	/CAPLK CAPLK PWR with Laser
	3761/3791	2	02TC010	10	T/W
	3776/3777 IS 386	1 / 2	02TC006	36	/CAPLK CAPLK
	3781	2	02TC002	04	T/W D/E
HEWLETT PACKARD	700-43/60/92/96	2	02TC006	61	/CAPLK CAPLK Power Required
	2392A	2	02TC006	42	/CAPLK CAPLK
	HIL	2	02TC013	65	/CAPLK CAPLK
	VECTRA	1 / 2	02TC000	01	/CAPLK CAPLK
IBM	PC XT & Clones	1 / 2	02TC001	00	/CAPLK CAPLK
	PC AT & Clones	1 / 2	02TC001	01	/CAPLK CAPLK
	PS/2 & Clones	1 / 2	02TC000	01 24	/CAPLK CAPLK
	3151	1 / 2	02TC008	22	102 Power with Laser
	3161/3163	1 / 2	02TC004	02	102
	3179-1	1 / 2	02TC004	03	T/W D/E Input Inhibit
	3179-2	1 / 2	02TC004	04	T/W Input Inhibit (5128)
	3180-1	1 / 2	02TC004	05	122 102 Input Inhibit (5128)
	3180-2	1 / 2	02TC004	06	T/W D/E Input Inhibit (5128)

**TurboWedge Genealogy**

<b>Terminal Manufacturer</b>	<b>Terminal Type</b>	<b>Model</b>	<b>Cable Number</b>	<b>ID</b>	<b>Keyboard Primary - Secondary Comments</b>
IBM	3191/92	1 / 2	02TC004	07	122 102
	3196	1 / 2	02TC004	08	122 102 Input Inhibit (5128)
	3197	1 / 2	02TC004	25	122 102
	3471/3472	1 / 2	02TC008	03	T/W D/E
	3476/3478	1 / 2	02TC008	08	122 102
	3477	1 / 2	02TC008	08	122 102 Inter Char. Delay=03
	3481	1 / 2	02TC008	08	122 102
	3481	1 / 2	02TC009	34	122 102 Input Inhibit (5128)
	3486/3487	1 / 2	02TC008	08	122 102 Inter Char. Delay = 02
	3486/3487	1 / 2	02TC009	08	122 102 Inter Char. Delay = 02 Input Inhibit (5128)
MEMOREX	1196/1475	1 / 2	02TC001	08	T/W
	2192	1 / 2	02TC001	30	T/W D/E
TELEX	191	1 / 2	02TC001	07	T/W D/E
	78X - 80X	1 / 2	02TC001	02	T/W D/E Input Inhibit
	1192	1 / 2	02TC001	03	T/W 122 D/E 122
	1196/1476	1 / 2	02TC001	08	T/W D/E
	1197	1 / 2	02TC001	25	T/W D/E
WYSE	30	2	02TC012	54	/CAPLK CAPLK Power Required
	ANSI -105 Keyboard	2	02TC012	51	/CAPLK CAPLK Power Required
	ASCII Keyboard	2	02TC012	52	/CAPLK CAPLK Power Required
	PC Enhanced -102 Keyboard	2	02TC012	53	/CAPLK CAPLK Power Required
	ANSI Enhanced -108 Keyboard	2	02TC012	56	/CAPLK CAPLK Power Required

**TurboWedge Genealogy - RS 232 CABLE CONFIGURATIONS**

<b>Cable Order #</b>	<b>Connector Type</b>	<b>Terminal Connector</b>	<b>Output</b>	<b>DTE / DCE</b>
02TC017	DB 9	Male	Single	DTE
02TC018	DB 9	Female	Single	DTE
02TC019	DB 25	Male	Single	DTE
02TC020	DB 25	Female	Single	DTE
02TC021	DB 9	Male	Single	DCE
02TC022	DB 9	Female	Single	DCE
02TC023	DB 25	Male	Single	DCE
02TC024	DB 25	Female	Single	DCE
02TC025	DB 9	Male	Dual	DTE
02TC026	DB 9	Female	Dual	DTE
02TC027	DB 25	Male	Dual	DTE
02TC028	DB 25	Female	Dual	DTE
02TC029	DB 9	Male	Dual	DCE
02TC030	DB 9	Female	Dual	DCE
02TC031	DB 25	Male	Dual	DCE
02TC032	DB 25	Female	Dual	DCE

**RS 232 CABLE NOTES:**

- For Correct Cable Configuration, Send to Compsee Customer Support the terminal to host interface requirements and pin-outs.
- Power Supply Required when interfacing via the RS 232 Communications Line.
- DCE or DTE refers to equipment that the Compsee cable is being connected with.